

Technical datasheet

Ribbed mat, fine

Basic information	Specification
Basic elastomer	natural rubber
Fabric ply	without ply or with 1 cotton fabric
Description/features	Bottom fabric-patterned, anti-slip properties due to the structure of the top
Format	Rolls: 3 mm available in: 10 m x 1 m and 10 m x 1.2 m
Colour	black or grey

Technical data	Standard term/Specification	Unit	Testing method
Density	n.a.	g/cm ³	DIN EN ISO 1183-1
Shore A	65	°Sh A	DIN ISO 7619-1
Tensile strength	n.a.	N/mm ²	DIN 53504
Elongation at break	n.a.	%	DIN 53504
Abrasion	n.a.	mm ³	DIN ISO 4649 method A
Temperature range	n.a.	°C	

Resistance	Standard term/Specification
Oil	⊖ respectively ⊕*
Fuels	n.sp.
Acids	n.sp.
Alkaline solution	n.sp.
Weather	⊖

Legend
⊕ ⊕ = particularly resistant ⊖ = not resistant n.sp. = not specified ⊕ = resistant n.a. = not applicable

Product-related special properties can be tested in our in-house laboratory. If necessary separate standards and testing standards deviating from DIN may be specified.
 * oil- and grease resistant qualities on request

All information based on current knowledge and experience. Information provided shall not exempt the contractor or user from conducting own tests. A legally binding warranty as to product features or its suitability for specific purposes may not be derived therefrom. Compliance with any proprietary rights as well as existing laws or regulations is the responsibility of the recipient of our products. No liability assumed for printing and any other errors. Technical data subject to change without notice. Reproduction or duplication of this document or its contents - whole or in part - is only permitted with express approval by company noltewerk. The German version of this data shall prevail. As of 1019.



elastomer
technology