





Supply range

Cleats and carriers profiles for rubber conveyor belts quality/design hot-cured

| Designation | Figure | Type | Dimensions [mm] | | | | Length of product ⁵⁾ [mm] | Number of designs [pcs] | Tool number ⁶⁾ | Edges (short side) |
|----------------|---|---------------------|-----------------|----|-----|---|---|----------------------------|---------------------------|--------------------|
| | | | A | B | C | R | | | | |
| Rectangle |  | 20x10 | 20 | 10 | - | - | 830 | 2 | no. 7 | Straight |
| | | | | | | | 1220 | 3 | no. 3 | |
| | | 20x8 ¹⁾ | 20 | 8 | - | 3 | 735 | 3 | no. 19 | Rounded |
| 18x5 | 18 | 5 | - | - | 558 | 2 | no. 34 | | | |
| Triangle |  | 23x10 | 23 | 10 | 2 | - | 970 | 3 | no. 12 | Straight |
| | | | | | | | 760 | 3 | no. 26 | |
| Trapeze form A |  | 24x12 | 24 | 12 | 15 | - | 820 | 2 | no. 2 | Straight |
| | | 36x15 | 36 | 15 | 15 | - | 550 | 3 | no. 4 | |
| | | 39x15 | 39 | 15 | 20 | - | 1170 | 2 | no. 1 | |
| | | 40x23 | 40 | 23 | 20 | - | 1170 | 2 | no. 10 | |
| | | 39x15 ³⁾ | 39 | 15 | 20 | - | 1450 | 4 | no. 28 | |
| | | 24x15 ⁴⁾ | 24 | 15 | 5 | 2 | 1080 | 20 | no. 32 | |
| | | 35x8 | 35 | 8 | 10 | 4 | 900 | 2 | no. 42 | |
| | | 24x12 ⁴⁾ | 24 | 12 | 5 | 2 | 1130 | 2 | no. 33 | Angled |
| Trapeze form B |  | 30x8 | 30 | 8 | 15 | - | 1210 | 3 | no. 8 | Straight |
| | | 30x10 | 30 | 10 | 15 | - | 550 | 3 | no. 17 | |
| | | 30x10 | 30 | 10 | 15 | - | 450 | 2 | no. 18 | |
| | | 30x12 | 30 | 12 | 15 | - | 880 | 2 | no. 14 | |
| | | 20x15 | 20 | 15 | 15 | - | 1200 | 2 | no. 24 | |
| | | 24x12 | 24 | 12 | 18 | - | 1050 | 2 | no. 30 | |
| | | 24x152 | 24 | 12 | 18 | - | 740 | 2 | no. 37 | |

- 1) The upper edges of the long cleats are fitted with a radius (R3).
- 2) The upper edge of the long side towards the bevel is fitted with a radius.
- 3) Any length of cleat possible by using inlays (edges may also either be straight or angled).
- 4) Both upper edges of the long side are fitted a radius.
- 5) Please note length of product. Production of a shorter cleat than mentioned in the specification (column: length of product) is possible at any time.
- 6) Please state tool number upon ordering.

page 1/3




All information based on current knowledge and experience. Information provided shall not exempt the contractor or user from conducting own tests. A legally binding warranty as to product features or its suitability for specific purposes may not be derived therefrom. Compliance with any proprietary rights as well as existing laws or regulations is the responsibility of the recipient of our products. No liability assumed for printing and any other errors. Technical data subject to change without notice. Reproduction or duplication of this document or its contents - whole or in part - is only permitted with express approval by company noltewerk. The German version of this data shall prevail. As of 0821.



rubber
conveyor belts


Supply range

Cleats and carriers profiles for rubber conveyor belts quality/design hot-cured

| Designation | Figure | Type | Dimensions [mm] | | | | Length of product ⁵⁾ [mm] | Number of designs [pcs] | Tool number ⁶⁾ | Edges (short side) | |
|------------------|---|-------|-----------------|----|-----|-----|--------------------------------------|-------------------------|---------------------------|--------------------|----------|
| | | | A | B | C | R | | | | | |
| Round |  | 20x10 | 20 | 10 | - | 10 | 800 | 2 | no. 13 | Rounded | |
| | | | | | | | 690 | 3 | no. 9 | | |
| | | 36x12 | 36 | 12 | - | - | 1310 | 4 | no. 23 | | |
| | | | | | | | | | | | Straight |
| | | 36x12 | 36 | 12 | - | 20 | 520 | 4 | no. 20 | | |
| | | | | | | | 1190 | 3 | no. 11 | | |
| | | | | | | | | | Angled | | |
| 35x8 | 35 | 8 | - | - | 870 | 3 | no. 27 | | | | |
| | | | | | | 705 | 4 | no. 29 | | | |
| Radius one side |  | 20x10 | 20 | 10 | - | 10 | 420 | 3 | no. 6 | Straight | |
| | | | | | | | 870 | 2 | no. 5 | | |
| | | | | | | | 1100 | 2 | no. 21 | | |
| Radius two sides |  | 22x7 | 22 | 7 | - | 6 | 450 | 2 | no. 15 | Rounded | |
| | | | | | | | | | | | |
| | | 35x8 | 35 | 8 | - | 8 | 685 | 4 | no. 16 | | |
| | | | | | | | 1330 | 3 | no. 22 | | |
| | | 35x8 | 35 | 8 | - | 8 | 670 | 2 | no. 25 | | |
| | | | | | | | 592 | 2 | no. 31 | | |
| | | 35x8 | 35 | 8 | - | 8 | 1180 | 4 | no. 35 | | |
| | | | | | | | | | | | |
| | | 30x12 | 30 | 12 | - | 12 | 570 | 2 | no. 36 | | |
| | | | | | | | | | | | |
| 35x8 | 35 | 8 | - | 8 | 886 | 4 | no. 38 | | | | |
| | | | | | | | | | | | |
| 35x8 | 35 | 8 | - | 8 | 346 | 2 | no. 43 | | | | |









- 1) The upper edges of the long cleats are fitted with a radius (R3).
- 2) The upper edge of the long side towards the bevel is fitted with a radius.
- 3) Any length of cleat possible by using inlays (edges may also either be straight or angled).
- 4) Both upper edges of the long side are fitted a radius.
- 5) Please note length of product. Production of a shorter cleat than mentioned in the specification (column: length of product) is possible at any time.
- 6) Please state tool number upon ordering.

All information based on current knowledge and experience. Information provided shall not exempt the contractor or user from conducting own tests. A legally binding warranty as to product features or its suitability for specific purposes may not be derived therefrom. Compliance with any proprietary rights as well as existing laws or regulations is the responsibility of the recipient of our products. No liability assumed for printing and any other errors. Technical data subject to change without notice. Reproduction or duplication of this document or its contents - whole or in part - is only permitted with express approval by company noltewerk. The German version of this data shall prevail. As of 0821.



Supply range

Cleats and carriers profiles for rubber conveyor belts quality/design cold-cured

| Designation | Figure | Type | Dimensions [mm] | | | | Transverse profile | | Longitudinal profile | |
|-------------|---|--------|-------------------------|-----|----|---|--|---|---|---|
| | | | A | B | C | R |  |  |  |  |
| | | | min. drum diameter (mm) | | | | | | | |
| Straight |  | T 20 | 40 | 20 | - | - | 150 | 180 | - | - |
| | | T 40 | 70 | 40 | - | - | 180 | 200 | - | - |
| | | T 55 | 80 | 55 | - | - | 160 | 200 | - | - |
| | | T 60 | 80 | 60 | - | - | 160 | 200 | - | - |
| | | T 75 | 80 | 75 | - | - | 200 | 300 | - | - |
| | | T 110 | 110 | 110 | - | - | 275 | 400 | - | - |
| | | T 140 | 160 | 140 | - | - | 400 | 450 | - | - |
| | | T 160 | 160 | 160 | - | - | 400 | 450 | - | - |
| | | T 180 | 160 | 180 | - | - | 400 | 450 | - | - |
| Angled |  | TS 40 | 70 | 40 | - | - | 160 | 200 | - | - |
| | | TS 55 | 80 | 55 | - | - | 160 | 250 | - | - |
| | | TS 60 | 80 | 60 | - | - | 160 | 250 | - | - |
| | | TS 75 | 80 | 75 | - | - | 200 | 300 | - | - |
| | | TS 110 | 110 | 110 | - | - | 275 | 400 | - | - |
| Cranked |  | TC 75 | 80 | 75 | - | - | 200 | 300 | - | - |
| | | TC 110 | 110 | 110 | - | - | 275 | 400 | - | - |
| | | TC 140 | 160 | 140 | - | - | 400 | 500 | - | - |
| | | TC 160 | 160 | 160 | - | - | 400 | 500 | - | - |
| | | TC 180 | 160 | 180 | - | - | 400 | 500 | - | - |
| Block |  | TB 25 | 37 | 25 | 12 | - | 180 | 200 | - | - |
| | | TB 37 | 75 | 40 | 35 | - | 450 | 550 | - | - |
| | | TB 40 | 80 | 40 | 10 | - | 250 | 315 | - | - |
| | | TB 50 | 75 | 50 | 25 | - | 315 | 450 | - | - |
| | | TB 60 | 80 | 60 | 10 | - | 200 | 300 | - | - |

