

Technical information

Processing possibilities transparent plastics

Material	Processing type											
	Laser cutting	Deep drawing	Cut (saw cut)	Thermo-forming	Cold beveling	Thermo-beveling	Adhere	Polish	CNC-milling	Water-jet-cutting	Drilling / thread cutting	Punching
PC		•	•	•	•	•	•	•	•	•	•	•
PC anti-static coating		•	•		•				•	•	•	
PC abrasion resistant coating			•			•			•	•	•	
PMMA GS	•	•	•	•		•	•	•	•	•	•	
PMMA XT	•	•	•	•		•	•	•	•	•	•*	
PETG		•	•	•		•	•	•	•	•	•	

* Tread-cutting not recommended as tread does not absorb [mechanical] forces

page 1 / 1

All information based on current knowledge and experience. Information provided shall not exempt the contractor or user from conducting own tests. A legally binding warranty as to product features or its suitability for specific purposes may not be derived therefrom. Compliance with any proprietary rights as well as existing laws or regulations is the responsibility of the recipient of our products. No liability assumed for printing and any other errors. Technical data subject to change without notice. Reproduction or duplication of this document or its contents - whole or in part - is only permitted with express approval by company noltewerk. The German version of this data shall prevail. As of 1017.



transparent
plastics