Technical datasheet

CeNit® 2380 Netting 6x6

Basic information	Specification
Covering material	PVC
Fabric insert	PES
Standard width	3,600 mm
Mesh width	6 x 6 mm
Colour	black
Description/features	Mesh for individual applications

Technical specification	Standard value/Specification	Unit	Testing standard
Grammage	ca. 420	g/m²	EN ISO 2286/2
Max. tensile strength (warp)	2,000	N/50mm	DIN EN ISO 1421
Max. tensile strength (weft)	1,600	N/50mm	DIN EN ISO 1421
Elongation at max. tensile strength (warp)	15	%	DIN EN ISO 1421
Elongation at max. tensile strength (weft)	15	%	DIN EN ISO 1421

Legend	
n.sp. = not specified	n.a. = not applicable

Prodct-related special properties can be tested in our in-house laboratory. If necessary separate standards and testing standards deviating from DIN may be specified.

All information based on current knowledge and experience. Information provided shall not exempt the contractor or user from conducting own tests. A legally binding warranty as to product features or its suitability for specific purposes may not be derived therefrom. Compliance with any proprietary rights as well as existing laws or regulations is the responsibility of the recipient of our products. No liability assumed for printing and any other errors. Technical data subject to change without notice. Reproduction or duplication of this document or its contents - whole or in part - is only permitted with express approval by company noltewerk. The German version of this data shall prevail. As of 0525.

elastomer technology

noltewerk GmbH & Co. KG · Mergenthalerstr. 15 · 48268 Greven · Germany · t +49 (2571)16-0 · info@noltewerk.de · noltewerk.com